

# HOSPITAL DRYER

## g560



<b>Capacity (litre)</b>	560L
<b>Exterior (high x wide x deep mm)</b>	1800 x 940 x 750
<b>Interior (high x wide x deep mm)</b>	1300 x 795 x 590
<b>Shelf size (wide x deep mm)</b>	789 x 556
<b>Shelves</b>	5
<b>Shelf positions</b>	10 per chamber
<b>Shelf spacing (mm) (variations upon request)</b>	80
<b>Fan Circulation specially designed for optimal drying</b>	1 fan system
<b>Heating (stainless sheathed element)</b>	1 x 2.2 kW
<b>Micro-Digital control (with digital readout and LCD)</b>	1
<b>Safety (safety overheat cut-out thermostat)</b>	Included
<b>User calibration facility</b>	Included
<b>Tamper proof control</b>	Included
<b>Temperature range</b>	Ambient + 5 °C to 80 °C
<b>Temperature accuracy</b>	± 0.1 °C at sensor. Chamber typically ±1.0 °C
<b>Electrical</b>	220-240 V, 50-60 Hz single phase (alternative power range available)



### Options Description

- tc Countdown to stop timer (not required if any p option selected)
- rs Allows RS communication to & from chamber control system (requires software & option)
- c Four Swivel Castors - Two lockable
- hf Hepa Filter (for a bacteria free drying system)
- td1 Tube dryer (1) one chamber with tubes: **Optional (108 tubes)**
- ps Pass through system with double door (rear&front door)
- s Extra shelf

