

INCUBATOR

i160

axyos

Capacity (litre)	160
Exterior [Stainless Steel Facia] (high x wide x deep mm)	860 x 876 x 700
Exterior refrigerated (high x wide x deep mm)	985 x 876 x 700
Interior [Stainless Steel] (high x wide x deep mm)	518 x 600 x 548
Shelf size (wide x deep mm)	595 x 545
Shelves	3
Shelf positions	5
Shelf spacing (mm)	80
Fan circulation	Included
Heating (stainless sheathed element)	0.7kW
Micro-Digital control (with digital readout and LCD)	Included
Temperature range	Ambient +5°C to 80°C (other ranges available)
Temperature accuracy	±0.1°C at sensor chamber typically ± 0.5°C
Electrical	220-240v , 50-60Hz single phase (alternative power ranges available)
Internal viewing door (Fully Sealed)	Included



Options Description

ac	°C alarm - Audible & visual for ±°C tolerances
ad	Door open alarm - audible & visual
c	Four Swivel Castors - Two lockable
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
f	Adjustable feet (cannot be installed if c selected)
v	Internal power supply for shaker or other similar appliance
vo	Door switch to deactivate internal power supply eg: turn off orbital shaker
s?	Extra Shelves
tp??	Sealed test hole installed in chamber for test cables (advise diameter in mm)
tc	Countdown to stop timer
to	Auto programmable start stop timer
r	°C control from +4 to 80°C (call for other °C options)
ct	Certificate of calibration and °C/time graph of test against Australian NATA traceable device
CO2	Micro Digital controlled CO2 percentage via an infra red sensor.

