

INCUBATOR

i75

axyos

Capacity (litre)	75
Exterior [Stainless Steel Facia] (high x wide x deep mm)	758 x 540 x 485
Interior [Stainless Steel] (high x wide x deep mm)	437 x 435 x 375
Shelf size (wide x deep mm)	428 x 350
Shelves	2
Shelf positions	4
Shelf spacing (mm)	80
Fan circulation	Optional
Heating (stainless sheathed element)	0.25kW
Micro-Digital control (with digital readout and LCD)	Included
Temperature range	Ambient +5°C to 80°C (other ranges available)
Temperature accuracy	±0.1°C at sensor chamber typically ± 0.5°C
Electrical	220-240v , 50-60Hz single phase (alternative power ranges available)



Options Description

ac	°C alarm - Audible & visual for ±°C tolerances
ad	Door open alarm - audible & visual
c	Four Swivel Castors - Two lockable
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
cn	Fan circulation for increased spatial accuracy & °C response
f	Adjustable feet (cannot be installed if c selected)
v	Internal power supply for shaker or other similar appliance
vo	Door switch to deactivate internal power supply eg: turn off orbital shaker
s?	Extra Shelves
tp??	Sealed test hole installed in chamber for test cables (advise diameter in mm)
tc	Countdown to stop timer
to	Auto programmable start stop timer
id	Internal perspex viewing door
ct	Certificate of calibration and °C/time graph of test against Australian NATA traceable device

