

<b>Capacity (litre):</b>	25
<b>Exterior [Stainless Steel Facia] (high x wide x deep mm)</b>	620 x 370 x 420
<b>Interior [Stainless Steel] (high x wide x deep mm)</b>	295 x 262 x 300
<b>Shelf Size (high x wide x deep mm)</b>	260 x 280
<b>Shelves</b>	2
<b>Shelf Positions</b>	3
<b>Shelf Space (mm)</b>	65
<b>Fan Circulation</b>	Optional
<b>Heating (stainless sheathed element)</b>	1.2kW
<b>Micro-Digital control (with digital readout and lcd)</b>	Included
<b>Temperature Range</b>	Ambient + 5°C to 200°C (other ranges available)
<b>Temperature Accuracy</b>	± 0.1°C at sensor
<b>Electrical</b>	220-240v , 50-60Hz single phase (alternative power ranges available)



## Options Description

250	Increased upper °C to 250°C maximum
at	°C alarm - Audible & visual for ±°C tolerances
ad	Door open alarm - audible & visual
c	Four Swivel Castors - Two lockable
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
cn	Fan circulation for increased spatial accuracy & °C response (25,75 & 140 series)
f	Adjustable feet (cannot be installed if w selected)
me	Hi power drying system for sample, glass or materials drying (Limits upper temp to 125°C)
s?	Extra Shelves
tp??	Sealed test hole installed in chamber for test cables (advise diameter in mm)
tc	Countdown to stop timer
to	Auto programmable start stop timer
ct	Certificate of calibration and °C/time graph of test against Australian NATA traceable device

