

Capacity (litre):	75
Exterior [Stainless Steel Facia] (high x wide x deep mm)	758 x 540 x 485
Interior [Stainless Steel] (high x wide x deep mm)	437 x 435 x 375
Shelf Size (high x wide x deep mm)	428 x 350
Shelves	2
Shelf Positions	4
Shelf Spacing (mm)	80
Fan Circulation	Optional
Heating (stainless sheathed element)	1.2kW
Micro-Digital control (with digital readout and lcd)	Included
Temperature Range	Ambient + 5°C to 200°C (other ranges available)
Temperature Accuracy	± 0.1°C at sensor
Electrical	220-240v , 50-60Hz single phase (alternative power ranges available)



Options Description

250	Increased upper °C to 250°C maximum
at	°C alarm - Audible & visual for ±°C tolerances
ad	Door open alarm - audible & visual
c	Four Swivel Castors - Two lockable
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
cn	Fan circulation for increased spatial accuracy & °C response (25,75 & 140 series)
f	Adjustable feet (cannot be installed if c selected)
me	Hi power drying system for sample, glass or materials drying (Limits upper temp to 125°C)
s?	Extra Shelves
tp??	Sealed test hole installed in chamber for test cables (advise diameter in mm)
tc	Countdown to stop timer
to	Auto programmable start stop timer
ct	Certificate of calibration and °C/time graph of test against Australian NATA traceable device

