

# WATERBATH

axyos

## w10



**Capacity (litre) filled** 10

**Exterior [Stainless Steel Facia]** 573 x 290 x 233  
(long x wide x deep mm)

**Interior [Stainless Steel]** 298 x 238 x 160  
(long x wide x deep mm)  
Rounded edges sterility & ease of cleaning

**Heating** 1.0kW  
(stainless sheathed element)

**Micro-Digital control** Included  
(with digital readout and lcd)

**Temperature Range** Ambient +5°C to 80°C  
(other ranges available)

**Temperature Accuracy** ±0.1°C at sensor. Bath typically ± 0.2°C

**Electrical** 220-240v 50-60Hz single phase  
(alternative power ranges available)

**User Calibration facility** Included

**Tamper proof control** Included

### Options Description

- at** °C alarm - Audible & visual for ±°C tolerances
- cr** Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
- cn** Circulation pump for increased spatial accuracy & °C response
- x** Circulation from bath to external device and returned (Std rating 12lpm - 2.07m head pressure)
- cl** Constant level device replacing evaporation
- pc** Programmable control system
- rc** Programmable ramp controller (cannot be installed if p selected)
- l** Removable gabled lid to suit bath
- r** °C control from +5 to 80°C (add circulation also)
- tc** Countdown to stop timer (not required if any p option selected)
- to** Auto programmable start stop timer (not required if any p option selected)
- dt** Tap to allow bath to be drained

