

WATERBATH

axyos

w15

Capacity (litre) filled	15
Exterior [Stainless Steel Facia] (long x wide x deep mm)	600 x 350 x 233
Interior [Stainless Steel] (long x wide x deep mm)	325 x 298 x 160 Rounded edges sterility & ease of cleaning
Heating (stainless sheathed element)	1.0kW
Micro-Digital control (with digital readout and lcd)	Included
Temperature Range	Ambient +5°C to 80°C (other ranges available)
Temperature Accuracy	±0.1°C at sensor. Bath typically ± 0.2°C
Electrical	220-240v 50-60Hz single phase (alternative power ranges available)
User Calibration facility	Included
Tamper proof control	Included



Options Description

at	°C alarm - Audible & visual for ±°C tolerances
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
cn	Circulation pump for increased spatial accuracy & °C response
x	Circulation from bath to external device and returned (Std rating 12lpm - 2.07m head pressure)
cl	Constant level device replacing evaporation
pc	Programmable control system
rc	Programmable ramp controller (cannot be installed if p selected)
l	Removable gabled lid to suit bath
r	°C control from +5 to 80°C (add circulation also)
tc	Countdown to stop timer (not required if any p option selected)
to	Auto programmable start stop timer (not required if any p option selected)
dt	Tap to allow bath to be drained

