

WATERBATH

axyos

w20

Capacity (litre) filled 20

Exterior [Stainless Steel Facia] 778 x 350 x 233
(long x wide x deep mm)

Interior [Stainless Steel] 503 x 298 x 160
(long x wide x deep mm)
Rounded edges sterility
& ease of cleaning

Heating 1.0kW
(stainless sheathed element)

Micro-Digital control Included
(with digital readout and lcd)

Temperature Range Ambient +5°C to 80°C
(other ranges available)

Temperature Accuracy ±0.1°C at sensor. Bath typically ± 0.2°C

Electrical 220-240v 50-60Hz single phase
(alternative power ranges available)

User Calibration facility Included

Tamper proof control Included



Options Description

at	°C alarm - Audible & visual for ±°C tolerances
cr	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
cn	Circulation pump for increased spatial accuracy & °C response
x	Circulation from bath to external device and returned (Std rating 12lpm - 2.07m head pressure)
cl	Constant level device replacing evaporation
pc	Programmable control system
rc	Programmable ramp controller (cannot be installed if p selected)
l	Removable gabled lid to suit bath
r	°C control from +5 to 80°C (add circulation also)
tc	Countdown to stop timer (not required if any p option selected)
to	Auto programmable start stop timer (not required if any p option selected)
dt	Tap to allow bath to be drained

