

# WATERBATH

axyos

## w40

<b>Capacity (litre) filled</b>	40
<b>Exterior [Stainless Steel Facia] (long x wide x deep mm)</b>	898 x 554 x 233
<b>Interior [Stainless Steel] (long x wide x deep mm)</b>	623 x 503 x 160 Rounded edges sterility & ease of cleaning
<b>Heating (stainless sheathed element)</b>	1.0kW
<b>Micro-Digital control (with digital readout and lcd)</b>	Included
<b>Temperature Range</b>	Ambient +5°C to 80°C (other ranges available)
<b>Temperature Accuracy</b>	±0.1°C at sensor. Bath typically ± 0.2°C
<b>Electrical</b>	220-240v 50-60Hz single phase (alternative power ranges available)
<b>User Calibration facility</b>	Included
<b>Tamper proof control</b>	Included



### Options Description

<b>at</b>	°C alarm - Audible & visual for ±°C tolerances
<b>cr</b>	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
<b>cn</b>	Circulation pump for increased spatial accuracy & °C response
<b>x</b>	Circulation from bath to external device and returned (Std rating 12lpm - 2.07m head pressure)
<b>cl</b>	Constant level device replacing evaporation
<b>pc</b>	Programmable control system
<b>rc</b>	Programmable ramp controller (cannot be installed if p selected)
<b>l</b>	Removable gabled lid to suit bath
<b>r</b>	°C control from +5 to 80°C (add circulation also)
<b>tc</b>	Countdown to stop timer (not required if any p option selected)
<b>to</b>	Auto programmable start stop timer (not required if any p option selected)
<b>dt</b>	Tap to allow bath to be drained

